



World's Smallest and Lightest 30,000 lm 3-Chip DLP™ 4K Projector* Streamlines Workflow Management

* Based on publicly available dimensions and weight for 3-Chip DLP™ 4K laser projectors with 26,000–35,000 lm brightness as of December 2020. PT-RQ35K Series has 30,500 lm (measurement, measuring conditions, and method of notation all compliant with ISO/IEC 21118: 2020 international standards, average value of all products when shipped).

■ Main Features

01 | Revolutionize Projection with Streamlined Workflow

Despite its high brightness and jaw-dropping image quality, PT-RQ35K is the lightest 3-Chip DLP™ 4K projector in its class and can be carried by two people, saving resources.

02 | Spellbinding Picture Quality

Two blue and one red laser expand color-space by 114 %^{*1}. Vivid reds and deep, natural blues heighten realism and help create an immersive projection experience faithful to the artist's intent.

03 | Original Cooling System for Projection Stability

Cooling system and finless radiator reinforce reliability over 20,000 hours^{**2} of maintenance-free operation. Backup input and laser failover circuitry maintain image display in mission-critical situations.



* Lens sold separately.

PT-RQ35K Series

	PT-RQ35K	PT-RZ34K
Light Output	30,500 lm ^{*3} / 32,000 lm (Center) ^{*4}	
Resolution	4K (3840 x 2400 pixels ^{*5})	WUXGA (1920 x 1200 pixels)

*1 In comparison to the PT-RQ32K according to internal research. *2 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment. *3 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *4 Average light-output value of all shipped products measured at center of screen in Normal Mode. *5 Maximum physical resolution with Quad Pixel Drive ON.

Streamlined Installation Workflow

With a body 40 %¹ smaller than the PT-RQ32K and footprint approximate to the PT-RQ22K, PT-RQ35K Series is easily carried by two people. Setup on AC 100–120 V² minimizes delays while AC 200–240 V is rolled out. Preactivated upgrade kits for Geo Pro³ expedite multi-screen calibration. You can check content on PC screen prior to projection via Remote Preview even while the projector is in Standby.

Spectacular Color for Multi-Screen Projection

Red and blue lasers achieve vivid reds and deep, natural blues with color-gamut reproduction expanded to 114 % [91 % DCI] over the PT-RQ32K. Newly developed Gradation Smoother reduces banding noise in gradients of shaded color. Improved edge-blending function allows you to adjust black border to screen curvature using up to 17 control points for precise black-level calibration.

¹ By cabinet volume according to internal research. ² Brightness limited to one-third of maximum when operating on 100–120 V power. ³ Register projector at PASS to download free Geometry Manager Pro software for Windows® with preactivated upgrade kits. ⁴ Projectors sold in some countries or regions require an ET-NUK10 Upgrade Kit to activate NFC function. ⁵ Optional AJ-WM50 Series Wireless Module required. ⁶ Autofocus function not supported on some devices. ⁷ Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. ⁸ Quiet Mode: 46 dB, brightness limited to 20,000 lm. ⁹ Excluding lenses for PT-RQ50K. ¹⁰ ET-SWA100 Early Warning functions bundled with Multi Monitoring & Control Software for Windows®. Purchase optional license at PASS to continue usage after free 90-day trial expires.

Specifications

Model	PT-RQ35K	PT-RZ34K
Projector type	3-Chip DLP™ projector	
DLP™ chip	Panel size 24.4 mm (0.96 in) diagonal (16:10 aspect ratio)	
	Display method DLP™ chip x 3, DLP™ projection system	
	Number of pixels 2,304,000 (1920 x 1200 pixels) x 3	
Light source	Laser diodes (Blue LD, Red LD)	
Light output	30,500 lm ⁷ /32,000 lm (Center) ⁸	
Time until light output declines to 50 % ⁹	20,000 hours (Normal), 24,000 hours (Eco), 26,000 hours (Quiet)	
Resolution	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)	WUXGA (1920 x 1200 pixels)
Contrast ratio ¹	20,000:1 (Full On/Full Off, Dynamic Contrast [3])	
Screen size (diagonal)	1.78–25.4 m (70–1,000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95	
Center-to-corner zone ratio ¹	90 %	
Lens	Optional (no lens included with this model)	
Lens shift ⁴	Vertical ±55 % (+78 %, +68 % with ET-D75LE95, ±48 % with ET-D3LEW200, ±44 % with ET-D75LE6/ET-D3LEW60) (powered)	
	Horizontal ±20 % (±15 % with ET-D75LE6/ET-D3LEW60/ET-D3LEW200, ±12 % with ET-D75LE95, ±25 %, 0 % with ET-D3LEU100) (powered)	
Keystone correction range	Vertical: ±45 ° (±40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.	
Terminals	SDI IN HDMI IN DVI-D IN MULTI PROJECTOR SYNC IN MULTI PROJECTOR SYNC OUT MULTI PROJECTOR SYNC IN terminal/ 3D SYNC 1 IN/OUT terminal (dual purpose) MULTI PROJECTOR SYNC OUT terminal/ 3D SYNC 2 OUT terminal (dual purpose) SERIAL IN SERIAL OUT REMOTE 1 IN REMOTE 1 OUT REMOTE 2 IN DIGITAL LINK LAN USB DC OUT Expansion slot	BNC x 1: 3G/HD-SDI input DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP) (Single-link only) — — BNC x 1 BNC x 1 D-sub 9-pin (female) x 1 for external control (RS-232C compliant) D-sub 9-pin (male) x 1 for link control (RS-232C compliant) M3 stereo mini-jack x 1 for wired remote control M3 stereo mini-jack x 1 for link control D-sub 9-pin (female) x 1 for external control (parallel) RJ-45 x 1 for network and DIGITAL LINK connection (HDBase™ compliant), 100Base-TX, compatible with Art-Net, PLink™ (Class 2), Deep Color, HDCP 2.2, 4K/60p signal input ⁵ RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible USB connector (Type A) x 1 for optional Wireless Module (AJ-WM50 Series)/USB Memory Stick USB Type A x 2 (for power supply, DC 5 V total of 2 A) SLOT 1/SLOT 2 (total two terminals, vacant) for interface boards, SLOT NX compatible SLOT (one terminal, vacant) for interface boards, SLOT NX compatible
Power supply	AC 200 V–240 V (Light output will decrease when using the projector with AC 100 V to AC 120 V)	
Power consumption	2,550 W (Standby: 14 W)	2,450 W (Standby: 13 W)
Operation noise ⁶	49 dB (Normal), 46 dB (Quiet)	
Dimensions (W x H x D)	Approx. 598 x 353 x 780 mm (23 17/32" x 13 29/32" x 30 23/32") (not including protruding parts)	
Weight ⁶	69.8 kg (153.9 lbs)	68.6 kg (151.2 lbs)
Operating environment	Operating temperature: 0–45 °C (32–113 °F ⁷), operating humidity: 10–80 % (no condensation)	
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Smart Projector Control for iOS/Android ¹⁰	

¹ Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. ² Average light-output value of all shipped products measured at center of screen in NORMAL Mode. ³ Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, Normal Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m³ of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment. ⁴ Lens shift is not supported on the ET-D3LEW50. ⁵ 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ34K. ⁶ Average value. May differ depending on the actual unit. ⁷ When optional AJ-WM50 wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).

Optional Accessories

- **Fisheye Lens** ET-D3LEF70
Note: Equipped with Auto Lens Identification Function.
- **Fixed-Focus Lens** ET-D75LE95 / ET-D3LEU100* / ET-D3LEW50*
* Equipped with Auto Lens Identification Function.
- **Zoom Lens**
ET-D3LEW200* / ET-D3LEW60* / ET-D75LE6 / ET-D3LEW10* / ET-D75LE10 / ET-D3LES20* / ET-D75LE20 / ET-D3LET30* / ET-D75LE30 / ET-D3LET40* / ET-D75LE40 / ET-D3LET80* / ET-D75LE8
* Equipped with Auto Lens Identification Function and Stepping Motor.
- **Stepping Motor Kit** ET-D75MKS10
Note: Calibration is required each time the lens is mounted.
- **Wireless Module** AJ-WM50 Series
Note: Product availability may vary by country or region.
- **DIGITAL LINK Switcher / Digital Interface Box**
ET-YFB200G / ET-YFB100G
Note: Not compatible with 4K signals.
- **Lens Fixed Attachment** ET-PLF10 (For ET-D3LEF70) / ET-PLF20 (For ET-D3LEU100/LEW200)
Note: This attachment may be required in some installation environments.
- **Early Warning Software** ET-SWA100 Series
Note: Part number suffix may differ depending on the license type.
- **NFC Upgrade Kit** ET-NUK10
Note: Product availability may vary by country or region.
- **High Frame Rate Upgrade Kit** ET-SUK10
Note: For PT-RQ35K only.
- **Interface Board**
Interface Board for 12G-SDI Input ET-MDN12G10
Interface Board for 12G-SDI Optical ET-MDNFB10
Interface Board for HDMI™ ET-MDNHM10
Interface Board for DVI Input ET-MDNVD10
Interface Board for DisplayPort™ ET-MDNPD10

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Windows® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. DisplayPort™ is a trademark owned by the Video Electronics Standards Association (VESA)® in the United States and other countries. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2020 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojectoranddisplay
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of December 2020.

RQ35Kseries_G1 Printed in Japan.

Smart Projector Control with NFC Function*4

Get a head start on projector setup even without AC power: just pair your smartphone via NFC and enter Projector ID and IP address. Smart Projector Control app expedites network connection⁵ with a QR Code displayed on Information Monitor, no SSID or password required. Adjust settings without menu projection and focus via smartphone camera⁶.



Engineered for Absolute Reliability

Dynamic Digital Control precisely adjusts red-laser output to image requirements and temperature. Projection stability is maintained by a dedicated cooling system. Finless radiator boosts cooling efficiency while shielded laser drive preserves image quality over 20,000 hours⁷ of maintenance-free projection. Backup input and failover circuitry maintain image display in mission-critical situations.

Other Features

- Information Monitor shows temp., runtime, signal data, error codes
- Quiet Mode⁸ ideal for theaters, museums, planetariums
- Geometric Adjustment with Free Grid
- Multi-Screen Support System and Multi-Unit Brightness & Color Control
- Shares Panasonic 3-Chip DLP™ projector lenses⁹
- 3D Professional (PT-RZ34K only)
- Multi Monitoring & Control Software with optional Early Warning functions¹⁰